



# Material Safety Data Sheet

Sonite 16

MSDS No. 916

Date Of Preparation: October 3, 2007

Revision: 0010

## Section 1 - Chemical Product and Company Identification

**Product/Chemical Name:** Sonite 16

**General Use:** Epoxy Curative

**Manufacturer:** Smooth-On Inc., 2000 St. John St., Easton PA 18042

Phone (610) 252-5800, FAX (610) 252-6200

**Emergency Contact:** Chem-Tel

Domestic 800-255-3924 International 813-248-0585

## Section 2 - Composition / Information on Ingredients

Component	CAS Number	ACGIH TWA	Exposure Limits OSHA PEL	Weight Percent (%)
Diethyltoluenediamine	68479-98-1	None Established	None Established	<b>80-90</b>
Diethylene Triamine	111-40-0	1 PPM	1 PPM	<b>10-20</b>

## Section 3 - Hazards Identification

### Potential Health Effects

HMIS	
H	2
F	1
R	1

**Primary Entry Routes:** Dermal

**Target Organs:** pancreas, liver, thyroid and eyes.

### Acute Effects

**Inhalation:** Vapors, which are not significant unless heated or sprayed can cause irritation to respiratory tract.

**Eye:** May cause irritation, redness, tearing, and blur vision. Prolonged vapor contact may cause conjunctivitis.

**Skin:** Contact will cause irritation, reddening, and swelling.

**Ingestion:** May have corrosive effects on the linings of the mouth and stomach: symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea.

**Carcinogenicity:** IARC, NTP, and OSHA do not list any components of this product as a carcinogen.

**Medical Conditions Aggravated by Long-Term Exposure:** Pre-existing skin disorders.

### Chronic Effects of Overexposure:

A two-year feeding study in rats showed diethyltoluenediamine caused effects in the pancreas, liver, thyroid and eyes. Also, an increase in the number of tumors in the liver and thyroid of male rats and in the liver and possibly mammary gland of female rats was found.

## Section 4 - First Aid Measures

**Inhalation:** Remove source(s) of contamination and move victim to fresh air.

**Eye Contact:** Flush eyes with plenty of water. If irritation persists, seek medical attention.

**Skin Contact:** In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse; seek medical attention if rash develops.

**Ingestion:** Do not induce vomiting unless instructed by a physician. Contact physician immediately

*After first aid, get appropriate in-plant, paramedic, or community medical support.*

### Section 5 - Fire-Fighting Measures

**Flash Point:** >200 °F (90°C)

**Flash Point Method:** CC

NFPA


**Flammability Classification:** Non-Flammable

**Extinguishing Media:** Water Fog, Dry Chemical, and Carbon Dioxide Foam

**Unusual Fire or Explosion Hazards:** None

**Fire-Fighting Instructions:** Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



### Section 6 - Accidental Release Measures

**Spill /Leak Procedures:** Dike and contain spill; absorb or scrape up excess into suitable container for disposal. Stop or reduce discharge if it can be done safely.

**Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1910.120).

### Section 7 - Handling and Storage

**Handling Precautions:** Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Use good general housekeeping procedures.

**Storage Requirements:** Store in cool dry, well-ventilated area.

### Section 8 - Exposure Controls / Personal Protection

**Engineering Controls:**

**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**Administrative Controls:**

**Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

**Protective Clothing/Equipment:** Wear chemically protective gloves, boots, and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics

### Section 9 - Physical and Chemical Properties

<b>Physical State:</b> Liquid	<b>Water Solubility:</b> Negligible:
<b>Appearance :</b> Amber to reddish brown liquid	<b>Boiling Point:</b> 390°F(199°C)
<b>Odor :</b> Ammonia odor	<b>% Volatile:</b> None Determined
<b>Vapor Pressure:</b> None Determined	<b>Freezing/Melting Point:</b> None Determined
<b>Vapor Density (Air=1):</b> >1	<b>Evaporation Rate:</b> None Determined)
<b>Specific Gravity (H<sub>2</sub>O=1, at 4 °C):</b> 0.984	

### Section 10 - Stability and Reactivity

**Stability:** This product is stable at room temperature in closed containers under normal storage and handling conditions.

**Polymerization:** Hazardous polymerization can not occur.

**Chemical Incompatibilities:** Strong acids and oxidizers.

**Conditions to Avoid:** Avoid contamination with water and other materials that react with amines.

**Thermal Decomposition Products:** Oxides of nitrogen, carbon monoxide and carbon dioxide.

### Section 11- Toxicological Information

**Acute Inhalation Effects:**

Human, inhalation, TC<sub>L</sub>: Not Determined

**Acute Oral Effects:** A two year feeding study in rats showed diethyltoluenediamine caused effects in the pancreas, liver, thyroid and eyes. Also, an increase in the number of tumors in the liver and thyroid of male rats and in the liver and possibly mammary gland of female rats was found.

**Reproductive Toxicity:** None Established

**Mutagenicity:** None Established

**Teratogenicity:** None Established

**Sensitization:** None Established

### Section 12 - Ecological Information

None Established

### Section 13 - Disposal Considerations

**Disposal:** This material must be disposed of in accordance with applicable Federal, state and local regulations.

### Section 14 - Transport Information

DOT	IATA	IMDG
<b>Shipping Name:</b> Diethylenetriamine	<b>Shipping Name:</b> Diethylenetriamine	<b>Shipping Name:</b> Diethylenetriamine
<b>UN #:</b> 2079	<b>UN #:</b> 2079	<b>UN #:</b> 2079
<b>Hazard Class:</b> 8	<b>Hazard Class:</b> 8	<b>Hazard Class:</b> 8
<b>Packing Group II</b>	<b>Packing Group II</b>	<b>Packing Group II</b>
<b>Label:</b> Corrosive	<b>Label:</b> Corrosive	<b>Label:</b> Corrosive

## Section 15 - Regulatory Information

### EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

CERCLA Hazardous Substance (40 CFR 302.4) listed specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112: None

SARA Toxic Chemical (40 CFR 372.65): None

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): None

**TSCA Inventory Status (40 CFR710):** All components of this formulation are listed in the TSCA Inventory.

### Canadian Regulations:

The Workplace Hazardous Materials Information System (W.H.M.I.S.) Classification for this product is: D1B, D2A, E

### States Right To Know, Substance List:

Idaho, Massachusetts, Minnesota, Pennsylvania, Washington and Wisconsin:

<u>Chemical Name</u>	<u>CAS #</u>	<u>% by Weight</u>
Diethylene Triamine	111-40-0	20% Max.

California Proposition 65: This product does not intentionally contain any chemicals, which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

## 16 - Other Information

**Prepared By:** Dominick J. Finocchio

**Title:** Technical Director

**Disclaimer:** The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.