



Materials Safety Data Sheet  
**IRON, STEEL & NICKEL BLACKENER**

===== I PRODUCT IDENTIFICATION =====

TRADE NAME (AS LABELED): **JAX IRON, STEEL AND NICKEL BLACKENER**

CHEMICAL NAMES, COMMON NAMES: NONE

SYNONYMS: NONE

MANUFACTURER'S NAME: JAX Chemical Company, Inc.

ADDRESS: 78-11 267<sup>th</sup> Street, Floral Park, New York 11004

BUSINESS PHONE: 718-347-0057

===== II HAZARDOUS INGREDIENTS =====

CHEMICAL NAME	CAS #	% w/w	EXPOSURE LIMITS IN AIR	
			TLV	PEL
			ACGIH	OSHA
Nitric Acid	7697-37-2	> 1.0	2 ppm	2 ppm
Selenious Acid	7783-00-8	> 1.0	0.2 mg/m <sup>3</sup>	0.2 mg(Se)/m <sup>3</sup>
Copper Sulfate	7758-98-7	0.5-2.5	1 mg(Cu)/m <sup>3</sup>	1.0 mg(Cu)/m <sup>3</sup>

THE REMAINING 93 to 97 % INGREDIENTS ARE NON-HAZARDOUS

===== III PHYSICAL PROPERTIES =====

VAPOR DENSITY: NO DATA                      EVAPORATION RATE (WATER = 1): SIMILAR TO WATER  
SPECIFIC GRAVITY: 1.02                      MELTING POINT or RANGE: LESS THAN 32° F  
SOLUBILITY IN WATER: SOLUBLE              BOILING POINT: GREATER THAN 212° F  
VAPOR PRESSURE, mm Hg @ 20 C: NO DATA  
APPEARANCE & COLOR: LIGHT BLUE LIQUID              pH: 1.7

HOW TO DETECT THIS SUBSTANCE (warning properties): At room temperature this product is light blue liquid with no odor. No unusual warning properties.

===== IV FIRE and EXPLOSION =====

**THIS PRODUCT IS NON-FLAMMABLE AND NON-COMBUSTIBLE**

FLASH POINT, F (method): N/A  
AUTOIGNITION TEMPERATURE, F: N/A  
FLAMMABLE LIMITS in air by volume, %: lower N/A upper N/A  
FIRE EXTINGUISHING MATERIALS:  
water spray: OK carbon dioxide: OK foam: OK  
dry chemical: OK halon: OK other:

SPECIAL FIRE FIGHTING PROCEDURES: If involved in fire, use water spray. Fire Fighters must use Self Contained Breathing Apparatus.  
UNUSUAL FIRE & EXPLOSION HAZARDS: Product may decompose at high temperatures to form toxic gases.

===== V HEALTH HAZARD INFORMATION =====

SYMPTOMS OF OVER EXPOSURE by route of exposure:  
INHALATION: Upper respiratory irritation. Metallic taste. Headache.  
CONTACT WITH SKIN or EYES: Irritation and/or reddening and to skin and eyes. Change in skin pigmentation.

SKIN ABSORPTION: This product does not skin absorb to any appreciable degree.

INGESTION: Irritation to the GI tract, nausea, vomiting.

INJECTION: Local irritation at the site of injection, possible systemic injury depending on dose. \*

-----  
HEALTH EFFECTS OR RISKS FROM EXPOSURE An explanation in lay terms.

ACUTE: This product cause may reddening, irritation, or burns to the eyes or skin. Irritation to the nose or throat may occur if you breath the product vapors. Headache, central nervous system depression, and giddiness and/or dizziness may result in sensitive individuals.

CHRONIC: Long term exposure to this product to may cause severe and/or persistent irritation and/or sensitizing to the eyes and skin. Irritation to the nose or throat. Skin color change. Lassitude, giddiness and dizziness may occur.

-----  
FIRST AID EMERGENCY PROCEDURES:

If spilled on skin or eyes, immediately begin decontamination with running water. Remove exposed or contaminated clothing, taking care not to contaminate eyes. Victim & rescuers must seek immediate medical attention. If chemical is in eyes, open victim's eyes while under gentle running water. Use sufficient force to open eye lids. Have victim "roll" eyes. Minimum flushing is for 15 minutes. If chemical is inhaled, remove victim to fresh air and use artificial respiration to support vital functions. Remove or cover gross contamination to avoid exposure to rescuer's. If chemical is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or can not swallow.

Victim of chemical exposure and all rescuers must be taken for medical attention. Take copy of label and MSDS to physician or health professional with victim.

-----  
SUSPECTED CANCER AGENT?

This product's ingredient's are / are not found on the following lists:

<u>OSHA Z-2 LIST</u>	<u>NTP</u>	<u>IARC</u>
NO	NO	NO

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Any preexisting skin irritation or dermatitis can be aggravated by exposure to this product. Upper respiratory disfunction may also be aggravated by inhalation of the vapors of this product.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms of exposure.

===== VI REACTIVITY DATA =====

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: NONE

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: None.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: N/A

