



# Material Safety Data Sheet

Sonite 19

MSDS No. 919

Date of Preparation: November 3, 2004

Revision: 0007

## Section 1 - Chemical Product and Company Identification

**Product/Chemical Name:** Sonite 19

**Other Designations:** Aliphatic Amine

**General Use:** Epoxy Curative

**Manufacturer:** Smooth-On Inc., 2000 St. John St., Easton PA 18042

Phone (610) 252-5800, FAX (610) 252-6200

**Emergency Contact:** Chem-Tel

Domestic 800-255-3924

International 813-248-0585

## Section 2 - Composition / Information on Ingredients

Component	CAS Number	ACGIH TWA	Exposure Limits OSHA PEL	Weight Percent (%)
3,3'[(oxy bis(2,1-ethanedioxy)) bis-1-propanamine	39423-51-3	None Established	None Established	98-100

## Section 3 - Hazards Identification

### ☞ ☞ ☞ ☞ ☞ Emergency Overview ☞ ☞ ☞ ☞ ☞

#### Potential Health Effects

**Primary Entry Routes:** Skin, inhalation of vapors

#### Acute Effects

**Inhalation:** vapors are irritating to respiratory tract.

**Eye:** can cause burns

**Skin:** will cause burns: may cause sensitization after prolonged or repeated use.

**Ingestion:** will cause severe damage to the mucous membranes if swallowed.

**Carcinogenicity IARC, NTP, and OSHA:** All components of this product have not been identified as a carcinogen or probable carcinogen.

**Medical Conditions Aggravated by Long-Term Exposure:** preexisting eye and skin disorders may be aggravated by exposure.

HMI	
H	3
F	1
R	0

## Section 4 - First Aid Measures

**Inhalation:** Remove to fresh air; if breathing is labored seek medical attention.

**Eye Contact:** Flush with water for 15 minutes; seek medical attention

**Skin Contact:** remove with soap and water: if redness or rash develops seek medical attention: Launder contaminated clothing before reuse.

**Ingestion:** do not induce vomiting; seek medical attention

*After first aid, get appropriate in-plant, paramedic, or community medical support.*

### Section 5 - Fire-Fighting Measures

**Flash Point:** 260°F (127°C)

**Flash Point Method:** PMCC

**Flammability Classification:** Non-Flammable

**Extinguishing Media:** Foam, Dry Chemical, and Carbon Dioxide

**Unusual Fire or Explosion Hazards:** None

**Hazardous Combustion Products:** Oxides of Nitrogen and Carbon when burned

**Fire-Fighting Instructions:** Do not release runoff from fire control methods to sewers or waterways.

**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.



### Section 6 - Accidental Release Measures

#### Spill /Leak Procedures

**Containment:** Dike and contain for later disposal. Do not release into sewers or waterways.

**Cleanup:** Scrape up excess.

**Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1910.120).

### Section 7 - Handling and Storage

**Handling Precautions:** Avoid prolonged or repeated eye and skin contact. Avoid breathing vapors and use only with adequate ventilation. Use good general housekeeping procedures.

**Storage Requirements:** Store in Closed containers. Use only with adequate ventilation.

### Section 8 - Exposure Controls / Personal Protection

#### Engineering Controls:

**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

#### Administrative Controls:

**Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

### Section 8 - Exposure Controls / Personal Protection (continued)

**Protective Clothing/Equipment:** Wear chemically protective gloves, boots, and aprons to prevent

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

### Section 9 - Physical and Chemical Properties

**Physical State:**

**Appearance and Odor:** Colorless low viscosity liquid, ammonia odor

**Vapor Pressure:** .001 mm/Hg @ 20°C

**Vapor Density (Air=1):** 8

**Specific Gravity (H<sub>2</sub>O=1, at 4 °C):** 1.01

**Water Solubility:** Soluble

**Boiling Point:** None Determined

**Freezing/Melting Point:** None Determined

**Evaporation Rate:** None Determined

### Section 10 - Stability and Reactivity

**Stability:** Sonite 19 is stable at room temperature in closed containers under normal storage and handling conditions.

**Polymerization:** Hazardous polymerization cannot occur.

**Chemical Incompatibilities:** Strong oxidizing agents, strong Lewis or mineral acids.

**Conditions to Avoid:** Mixing with epoxies under uncontrolled conditions.

**Hazardous Decomposition Products:** Thermal oxidative decomposition of can produce: Oxides of Nitrogen and Carbon when burned.

### Section 11 - Toxicological Information

**Toxicity Data:\***

**Eye Effects:** can cause burns

**Skin Effects:** will cause burns

**Mutagenicity:** None Determined

**Teratogenicity:** None Determined

### Section 12 - Ecological Information

None Determined

### Section 13 - Disposal Information

**Disposal:** Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

### Section 14 - Transport Information

DOT	IATA	IMDG
<b>Shipping Name:</b> Alkaline Amine N.O.S. (Polyether diamine)	<b>Shipping Name:</b> Alkaline Amine N.O.S. (Polyether diamine)	<b>Shipping Name:</b> Alkaline Amine N.O.S. (Polyether diamine)
<b>UN #:</b> 2735	<b>UN #:</b> 2735	<b>UN #:</b> 2735
<b>Hazard Class:</b> 8 Packing Group II	<b>Hazard Class:</b> 8 Packing Group II	<b>Hazard Class:</b> 8 Packing Group II
<b>Label:</b> Corrosive	<b>Label:</b> Corrosive	<b>Label:</b> Corrosive

### Section 15 - Regulatory Information

#### EPA Regulations:

**RCRA Hazardous Waste Number:** Not listed (40 CFR 261.33): This material is not considered a hazardous material under RCRA.

**RCRA Hazardous Waste Classification (40 CFR 261):** Not classified

**CERCLA Hazardous Substance (40 CFR 302.4)** unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

**CERCLA Reportable Quantity (RQ),** None

**SARA 311/312 Codes:** None

**SARA Toxic Chemical (40 CFR 372.65):** None

**SARA EHS (Extremely Hazardous Substance) (40 CFR 355):** Not listed,

**TSCA Inventory Status (40CFR710):** All components of this formula are on the TSCA inventory

#### State Regulations:

California Proposition 65: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

#### Canadian Regulations:

DSL: Included on Inventory

WHMIS Hazard Classification: Class D Division 2B, Class E Corrosive

WHMIS Symbols: Test tube/hand, Stylized T

### Section 16 - Other Information

**Prepared By:** Dominick J. Finocchio

**Title:** Technical Director

**Disclaimer:** The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.