

**MATERIAL SAFETY DATA SHEET**

Manufacturer: Price-Driscoll Corporation  
 17 Industrial Drive, Waterford, CT 06385  
 Tel: 800 442-3575 Fax: 800 447-3557

EMERGENCY PHONE: INFOTRAC 1 800 535-5053

---

<b>Product Name:</b>	<b>Eject-It #34 Carnauba Wax Release</b>	<b>Date: March 2007</b>
<b>Description:</b>	<b>Synthetic wax release for thermoset resins</b>	<b>Revision: August 2011</b>
<b>Product Series:</b>	<b>Spectrum Series</b>	
<b>Form:</b>	<b>Aerosol Cans, Net Weight: 16 oz.</b>	

---

**Hazardous Ingredients**

<u>CHEMICAL NAME</u>	<u>CAS#</u>	<u>OSHA PEL</u>	<u>% (Range)</u>
Trichloroethylene*	79-01-6	100 ppm	80 – 90 %
Propane	74-98-6	1000 ppm	5 – 15 %
Synthetic Wax	(mixtures)	N/A	2 – 10%

\*Contains no ozone depleting chemicals.  
 All components of this product are listed on the TSCA directory

---

**Physical/Chemical Characteristics**

Appearance & Odor	Water-white liquid, in aerosol can, halogenated hydrocarbon odor
Boiling Point	Range: 20°– 189° F
Vapor Pressure (psig)	40.5 psig @ 70° F
Specific Gravity (H <sub>2</sub> O = 1)	1.18
Solubility in Water	Nil
Percent Volatile by Weight	94

---

**Health Hazard Data****Effects of Overexposure**

**Ingestion:** Unlikely route of entry since product is an aerosol. (In large amounts, narcosis or death if untreated.)

**Inhalation:** Giddiness, dizziness, and possible narcosis. High levels of exposure may cause unconsciousness and may be immediate hazard to life.

**Skin Contact:** Temporary irritation, defatting of skin

**Eye Contact:** May cause pain and temporary irritation.

**Emergency First Aid Procedures**

**Eyes:** Flush with plenty of water. If irritation persists, seek medical attention.

**Skin:** Wash off in flowing water or shower. Remove and launder affected clothing prior to reuse.

**Ingestion:** Do not induce vomiting. Get medical attention.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

---

**Fire Fighting Measures**

Flammable Limits in Air:	LEL: N/A	UEL: N/A	Flash Point: None
Hazardous Combustion Products:	May include but are not limited to hydrogen chloride, traces of phosgene, chlorine and carbon monoxide.		
Extinguishing Media:	Water fog or fine spray. Carbon dioxide, dry chemical, foam.		
Other Flammability Information:	Container may vent and/or rupture due to fire. Vapors are heavier than air and may travel a long distance and accumulate in low-lying areas.		
Fire Fighting Instructions:	Keep people away. Isolate fire area and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Contain firewater run-off if possible.		

---

### Reactivity Data

**Stability:** Stable  
**Incompatibility (materials to avoid):** Avoid contact with metals such as: aluminum powders, magnesium powders, potassium, sodium, and zinc powder.  
**Hazardous Combustion By-Products:** (See "fire fighting measures" listed above)  
**Hazardous Polymerization:** Will not occur.  
**Conditions to Avoid:** Avoid direct sunlight or ultraviolet sources. Avoid open flames, welding arcs, or other high temperature sources which induce thermal decomposition.

---

### Precautions for Safe Handling and Use

**Steps to be taken in case material is spilled or released:**

Avoid breathing vapors. Evacuate area until vapor has dispersed. Remove all sources of ignition. Stop or reduce discharge if it can be done safely.

**Handling:** Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Do not use near ignition sources. Contents are under pressure. Do not puncture, incinerate, expose to open flame or temperature above 120°F. Keep out of direct sunlight. For industrial use only. Keep out of reach of children. Store in a well-ventilated place, Keep container tightly closed. Read label precautions. Do not remove or deface label.

**Storage:** Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperature above 120°F.

**Disposal:** Dispose according to Local, State and Federal regulations.

**Ventilation:** Local and mechanical exhaust -- use sufficient ventilation to keep employee exposure below recommended limits.

**Skin protection:** The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with the skin.

**Eye protection:** Proper eye protection should be worn in any type of industrial operation, such as splash-proof face shield or goggles.

**Respiratory:** NIOSH or other approved respirator is required in the absence of proper environmental control

---

California Proposition 65: This product contains a chemical known to the State of California to cause cancer. Trichloroethylene has been extensively studied for chronic effects in animals. While there are studies in which tumors were induced in mice, there is no documented evidence that exposure to trichloroethylene produces cancer in humans. Trichloroethylene is listed in Group 2A by IARC but is not listed by NTP or OSHA.

---

### SARA Title III Reporting

This product contains the following chemicals required to be reported under SARA Title III, Section 313: Trichloroethylene. (Reporting requirements under section CERCLA Section 304 are 1000 pounds or over),

---

**Other Information:** HMIS Classification: 2, 1, 0, B  
DOT Hazard Classification: ORM-D  
DOT Shipping Name: Consumer Commodity

---

**Manufacturer's Statement:** This information contained herein is believed to be correct as of issue date. Manufacturer shall not be liable for damages arising out of, or in connection with the information obtained herein. It is intended to assist in the normal, safe usage of product. No warranty of any kind is expressed or implied as to the accuracy, completeness or adequacy of the information obtained herein.