SCULPT NOUVEAU

Date Revised 04-03-12





Material Safety Data Sheet Metal Wax - All colors

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:

SCULPT NOUVEAU METAL PASTE WAX

MANUFACTURED BY:

SCULPT NOUVEAU

570 N. Tulip St.

Escondido, CA 92025 USA

Product Information Contact Information: (800) 728-5787 (8-5pm PST)

Fax Number: (760) 741-1074

www.sculptnouveau.com

24 HOUR TRANSPORTATION EMERGENCY NUMBER: CHEMTREC

800-424-9300 U.S. & CANADA 202-483-7616 INTERNATIONAL

2. COMPOSITION / INFORMATION ON INGREDIENTS

DESCRIPTION	CAS NUMBER	WEIGHT%
Carnauba & Microcrystalline wax blend	8015-86-9 63231-60-7	±20
Stoddard Solvent Gum Turpentine Benzene Colored Oxides	8052-41-3 8006-64-2 71-43-2 13463-67-7	±72 ±4 <.1 ±4

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Firm solid paste, colored or clear. Irritating or burning to eyes and skin.

EYE CONTACT: Irritation and possible burns upon direct contact.

SKIN CONTACT: Irritation and possible sensitization with certain individuals.

INGESTION: Irritation and possible burns to the gastrointestinal tract. Other possible symptoms include nausea, vomiting, abdominal pain. Significant absorption may cause sleepiness and pulmonary edema.

INHALATION: Toxic fumes are not normally generated. If inhalation of vapor concentrations occur, headache and nausea may occur.

CHRONIC: Not established.

4. FIRST AID MEASURES

EYE CONTACT: Flush immediately with clean water. Continue for at least 15 minutes. Consult a doctor.

SKIN CONTACT: Remove contaminated clothing. Wash exposed area with soap and water.

INHALATION: Remove to fresh air and seek medical attention if necessary.

INGESTION: DO NOT induce vomiting unless directed to by medical personnel. Never administer anything by mouth to an unconscious person. If breathing is difficult, give oxygen. Seek medical attention.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: TCC 102° F

FLAMMABLE LIMITS: LEL - .7 UEL - 6.0

EXTINGUISHING MEDIA: CO2 Foam

FIRE & EXPLOSION HAZARDS: Closed containers may burst when exposed to extreme heat. Isolate from heat, sparks, and open flame.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED: Review current, local, state and federal laws, codes, statutes, and regulations to determine appropriate agencies to be notified, and the conditions under which they are to be notified. Wear recommended protective equipment. Collect material into metal container. Avoid sparks or flame. Wipe off residue with rag.

WASTE DISPOSAL METHODS: Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Wastes and its solutions are assigned EPA Hazardous Waste Number D001. The wastes can be disposed of through a licensed waste disposal company.

HANDLING AND STORAGE

Wear protective equipment when handling. Store at room temperature in tightly closed containers. Store in dry area designated for flammable liquids. Avoid sources of ignition and prevent electrostatic discharge. No smoking.

8. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (type): Avoid

breathing vapor.

LOCAL EXHAUST VENTILATION: Use in well

ventilated areas.

MECHANICAL VENTILATION: No information

SPECIAL VENTILATION: N/A

PROTECTIVE GLOVES: Rubber

EYE PROTECTION: Use goggles or face

shield. Avoid contact w/eyes

OTHER PROTECTIVE EQUIP:

Rubber/plastic apron to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:

FLASHPOINT:

AUTO IGNITION:

MELTING POINT:

SOLUBILITY IN WATER:

VAPOR DENSITY:

SOLID CONTENT:

V.O.C. (g/l. by wt.):

Firm solid paste, characteristic odor

102°F

Approximately 440°F

>100°F

Insoluble

>1

±20%

3.95

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Keep away from all sources of heat

INCOMPATIBILITY (materials to avoid): Strong acids, alkalis, halogens, oxidents

HAZARDOUS DECOMPOSITION PRODUCTS: Toxic gases - carbon dioxide and or carbon monoxide

HAZARDOUS POLYMERIZATION: Will not occur

11. TOXICOLOGICAL INFORMATION

Inhalation or ingestion of this product are harmful. This product may irritate mucosas, the upper respiratory tract, eyes and skin. Exposure symptoms may include stinging and irritated eyes, mouth, nose and throat, respiratory disorders, dizziness, headache and nausea. Ingestion of even a small amount of this product may cause health disorders including stomach pain, nausea and diarrhea.

12. ECOLOGICAL INFORMATION

- 1. □ is product is biodegradable.
- 2. □ is product has the potential to bio-accumulate.
- 3. Toxic to □sh

13. DISPOSAL CONSIDERATIONS

Observe national and local requirements. Residues should be disposed of in the same manner as the substance/product. Contact the appropriate agency for speci □c information. Recycle, incinerate, or use hazardous waste management facility for disposal. EPA Waste No. D001

14. TRANSPORT INFORMATION

DOT & UN No. HAZARDOUS Flammable Solid, N.O.S., (Contains Stoddard Solvent) 4.1 UN1325 PACKING GROUP: III OSHA: CLASS II Combustible Liquid

15. REGULATORYINFORMATION

OSHA HAZARD COMMUNICATION RULE 29 CFR 1910.1200; Refer to section 2

TSCA (TOXIC SUBSTANCES CONTROL ACT): Components of this product - listed on the TCSA Inventory

CERCLA (Comprehensive Response compensation and Liability Act, 40 CFR 117, 302: Refer to section 6

16. OTHER INFORMATION

NFPA RATINGS: HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0



The Compleat Sculptor, Inc.

"You supply the talent, We'll supply the rest."
90 Van Dam Street • New York, NY 10013
(212) 243-6074 • Fax (212) 243-6374 • (800) 9-SCULPT
www.SCULPT.com